

**Grounding Kit for 1 5/8 Corrugated Coaxial Cable Spring Type**

**Electrical Specifications**

Peak Current	100,000 Amps
Current Handling Test Method	MIL-STD-1757
Lightning Protection Test Method	IEC-1024-1

**Mechanical Specifications**

Normal Size	1 5/8 Coaxial Corrugated Cable
Cable Contact Part	Copper Band and Stainless Steel Clamp
Lug Type	2-hole M8 (with Screws), Tin-Coated Copper
Cable Length	600 mm (800 / 1000 / 1500 mm Optional)
Cable Diameter	16 mm <sup>2</sup> (25 mm <sup>2</sup> Optional)
Cable Material	Copper
Insulator Material	PVC

**Environmental Durability**

Anti-Corrosion Level	≥ 500 Hours in Salt Spray Chamber
UV Resistance	≥ 1000 Hrs
Operating Temperature	-50°C to + 85°C

**Packaging Information**

Standard Package Includes Metal Hardware and Sealing Material	
Sealing Material: PVC Tape 5 cm x 1000 cm, Butyl Rubber Tape 7 cm x 60 cm	
Package Quantity	1 Set in a Bag
Unit Weight (Metal Parts)	0.158 kg
Unit Weight (including Sealing Material)	0.413 kg

