

N Male for S-Flex 1/4" Soldering Jumper
Electrical Specifications

Impedance	50 Ω
Frequency Range (MHz)	DC ~ 3 GHz
VSWR	≤ 1.10 (0.8 ~ 2.2GHz)
	≤ 1.15 (DC ~ 3GHz)
Return Loss	≤ -28 dB (2GHz)
	≤ -21 dB (2GHz)
PIM 3rd Order	≤ -155 dBc (2 x 43 dBm)
Insertion Loss	≤ 0.05 (0.8 ~ 1 GHz)
	≤ 0.08 (1 ~ 2.2 GHz)
	≤ 0.15 (2.2 ~ 3 GHz)
Working Voltage	2700 V (50 Hz AC)
Withstand Voltage	4000 V (50 Hz AC)
Outer Contact Resistance	< 1.5 M Ω
Inner Contact Resistance	< 1.5 M Ω
Insulation Resistance	≥ 5000 M Ω

Mechanical Specifications

Assembly Attachment Durability	≥ 50 Cycles
Interface Durability	≥ 500 Cycles
Insertion Force	≥ 30 N
Connector Retention Torque	1.4 N-m
Connector Retention Tensile Force	450 N
Water Resistance	IP68
Operating Temperature	-55 ~ +80 $^{\circ}$ C

Material and Plating

Inner Conductor	QSn6.5-0.1, Silver Plated
Outer Conductor	HPb59-1, Trimental Plating(Copper-Tin-Zin)
Insulation	PTEE
Gasket	Silicon Rubber

